

Plockmatic - System 70

Specifications



BM 60 Binder

Capacity	22 sheets of 80 gsm (20 lb Bond)
Speed	Up to 1800 sets/hour
Sheet size, max	338 x 458 mm (13.3 x 18")
Sheet size, min	138 x 210 mm (5.4 x 8.25")
Paper weight, max	250 gsm (90 lb Cover)
Paper weight, min	60 gsm (16 lb Bond)
Stapler modes	Saddle, edge and corner stapling
Stapler heads	2
Staples	210 Chisel pointed
Error detection	Low staple and jam
Dimensions incl. base and belt stacker, H x W x D	960 x 1230 x 500 mm (37.8 x 48.4 x 19.7")
Weight	55 kg (121 lb)

Plockmatic 104 Squarefold

Capacity	22 sheets of 80 gsm (20 lb Bond)
Speed	Up to 1800 sets/hour
Squarefolding modes	3 and by-pass
Booklet size, max	240 x 325 mm (9.4 x 12.8")
Booklet size, min	100 x 120 mm (3.9 x 4.7")
Dimensions incl. base, H x W x D	930 x 575 x 560 mm (36.6 x 22.6 x 22")
Weight	42 kg (92 lb)

Plockmatic - System 70

Power requirements

BM 60 Binder

Voltage	Tolerance	Current	Frequency
100 V	-10 / +6%	1 A	50-60 Hz
110 V	-10 / +6%	1 A	50-60 Hz
120 V	-10 / +6%	1 A	50-60 Hz
127 V	-10 / +6%	1 A	50-60 Hz
220 V	-10 / +6%	0.5 A	50-60 Hz
230 V	±10%	0.5 A	50-60 Hz

Plockmatic 104 Squarefold

Voltage	Tolerance	Current	Frequency
100 V	-10 / +6%	2 A	50-60 Hz
110 V	-10 / +6%	2 A	50-60 Hz
120 V	-10 / +6%	2 A	50-60 Hz
127 V	-10 / +6%	2 A	50-60 Hz
220 V	-10 / +6%	1 A	50-60 Hz
230 V	±10%	1 A	50-60 Hz